



2N® Access Commander Box

2N® Access Commander Box is a fully plug and play solution, ideally suited to SMB installations. The software is pre-installed on a mini-pc with ample resources to accommodate up to 2000 devices. You don't need to arrange separate server host hardware or access to an existing server for installation.

- · Plug and play deployment
- No server needed
- Designed for SMB installations

Variant



Technical Parameters

General

Introduction	The 2N® Access Commander Box is an
	access control software pre-installed on an
	ultra-compact, small and powerful computer.

PC specifications Dimension 56.1 x 107.6 x 114.4 mm (0.69 L) CPU 2.24 GHz (Intel® Celeron® Processor J3160) Hard drive 120 GB (2.5" SSD SATA III) RAM 4 GB (DDR3 SODIMM memory) VGA and HDMI Gigabit LAN port Connectors Mounting VESA mounting bracket Operating temperature 0°C to +35°C -20°C to +60°C Storage temperature

Limitations

Connected devices	2,000*
Users	100,000*
Users per group	1,500
	*Applies only to Access Commander version 2.0 or higher

PC specifications

Optimized for	Google Chrome browser (version 60 and higher)
Other supported browsers	Mozilla Firefox (version 55 or higher), Microsoft Edge (version 40 and higher)

Warranty

5-years warranty see

https://www.2n.com/en_GB/support/warranty-and-repairs